

Walraven BISOFIX® CF Cold FixPoint Clamp

(E0503)



Features & benefits

- insulated cold clamps made of pressure-resistant Polyurethane foam
- integral foam inner recess for mounting of the pressure flange
- outer link plates (galvanized) for connection to two piece set by crossbars
- high axial force absorption by the site welded to the pipe pressure flange
- durable materials ensure a long-term and reliable operation security
- PUR foam density ca. 250 kg/m³
- flammability class B2 (DIN 4102)
- K value 0.042 W/mK at 0 °C

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length	Maximum Allowed Load Faz
<i>Reference letter</i>	<i>D</i>	<i>G</i>	<i>W x H x L</i>	<i>Fa,z</i>
<i>Unit description</i>	<i>(mm)</i>		<i>(mm) x (mm) x (mm)</i>	<i>(N)</i>
0881076	76.10	None	100 x 137 x 203	3600
0881088	88.90	None	210 x 150 x 105	4300
0881114	114.30	None	275 x 195 x 115	6900
0881133	133	None	295 x 220 x 120	7700
0881139	139.70	None	300 x 220 x 130	8100
0881159	159	None	310 x 240 x 130	9200
0881168	168.30	None	325 x 255 x 135	9700
0881219	219.10	None	450 x 340 x 205	23000
0881273	273	None	500 x 400 x 210	28000
2210000		None	50 x 50 x 230	