

Walraven WDI2R Drop-in Anchor

(L0321)

reduced length drop-in anchor with a lip collar



Features & benefits

- European Technical Assessment according to EAD 330747-00-0601 (May 2018) for fasteners for use in concrete for redundant non-structural systems.
- increased productivity – the reduced 25mm anchor length minimizes drilling depth and speeds up installation
- approved applications in precast prestressed hollow core slabs
- fire resistance class R30-R120 for design of anchorages under exposure to fire
- complies with VdS CEA 4001: 2024-01 (08) for applications with sprinkler systems in concrete elements
- substrate type: cracked concrete, non-cracked concrete
- for loads and more information, refer to the product data sheet and/or the ETA report
- material: steel

Product Number	Thread Size	Thread Type	Total Width x Total Height x Total Length	Drill Hole Diameter	Standard Embedment Depth	Minimum Substrate Thickness
<i>Reference letter</i>	<i>TS</i>	<i>TT</i>	<i>W x H x L</i>	<i>d0</i>	<i>hnom</i>	<i>hmin</i>
<i>Unit description</i>			<i>(mm) x (mm) x (mm)</i>	<i>(mm)</i>	<i>(mm)</i>	<i>(mm)</i>
6103310825	M8	Metric	11 x 11 x 25	10	≥ 25	80
6103311025	M10	Metric	13 x 13 x 25	12	≥ 25	80
6103311225	M12	Metric	16 x 16 x 25	15	≥ 25	80